

THREADED ROD



ALL THREAD ROD

Model ATR

SIZE:

1/4" thru 1 1/2"

FINISH:

Plain, Electro-zinc plated, Stainless Steel, & Hot Dip Galvanized

FUNCTION:

Attaches hangers to structural attachments without threading the rod

NOTES:

1. ROD ENDS TO BE DEBURRED
2. UNC-2A THREAD
3. MATERIAL REQUIREMENTS:
 LOW CARBON STEEL MATERIAL PER ES-136:
 -TENSILE STRENGTH-58,000 PSI MIN.
 -YIELD STRENGTH-36,000 PSI MIN.
4. ENSURE PRODUCT MEETS LOAD REQUIREMENTS PER ES1182.

FEATURES:

- All Thread Rod manufactured by Elite Components meets the minimum physical requirements of (ASTM A36 & A307)
- 1/4" to 1" ATR is produced from 1006/1008/1010 steel.
- All Zinc Threaded Rod is plated according to (ASTM B633), and meets the specification of FeZn 8 SC2 – Type III
- All Stainless Steel Rod (Type 304) is manufactured in accordance to (ASTM A193)
- All Hot Dip Galvanized Rod is manufactured in accordance to (ASTM A153)

All Thread Rod: Weights (LBS) • Dimensions (IN) • Length (FT)

ITEM CODE PLAIN	ITEM CODE EG	ITEM CODE STAINLESS	ITEM CODE HD*	THREAD SIZE	WEIGHT / FT.	LENGTH	TUBE QTY PCS/FT.
ATR02506B	ATR02506Z			1/4- 20	0.12	6	50/300
ATR02510B	ATR02510Z			1/4- 20	0.12	10	50/500
ATR02512B	ATR02512Z			1/4- 20	0.12	12	50/600
		ATR03703SS		3/8- 16	0.291	3	20/60
		ATR03706SS		3/8- 16	0.291	6	20/120
ATR03706B	ATR03706Z			3/8- 16	0.291	6	25/150
ATR03710B	ATR03710Z			3/8- 16	0.291	10	25/250
		ATR03712SS		3/8- 16	0.291	12	20/240
ATR03712B	ATR03712Z			3/8- 16	0.291	12	25/300
		ATR05003SS		1/2- 13	0.522	3	12/36
ATR05006B	ATR05006Z	ATR05006SS		1/2- 13	0.522	6	12/72
ATR05010B	ATR05010Z			1/2- 13	0.522	10	12/120
ATR05012B	ATR05012Z	ATR05012SS	ATR00512HD	1/2- 13	0.522	12	12/144
ATR06206B	ATR06206Z	ATR06206SS		5/8- 11	0.837	6	8/48
ATR06210B	ATR06210Z			5/8- 11	0.837	10	8/80
ATR06212B	ATR06212Z	ATR06212SS	ATR00612HD	5/8- 11	0.837	12	8/96
ATR07506B	ATR07506Z	ATR07506SS		3/4- 10	1.224	6	5/30
ATR07510B	ATR07510Z			3/4- 10	1.224	10	5/50
ATR07512B	ATR07512Z	ATR07512SS		3/4- 10	1.224	12	5/60
ATR08706B	ATR08706Z			7/8- 9	1.692	6	4/24
ATR08710B	ATR08710Z			7/8- 9	1.692	10	4/40
ATR08712B	ATR08712Z			7/8- 9	1.692	12	4/48
ATR10006B	ATR10006Z			1 - 8	2.204	6	3/18
ATR10010B	ATR10010Z			1 - 8	2.204	10	2/20
ATR10012B	ATR10012Z			1 - 8	2.204	12	2/24
ATR11206B	ATR11206Z			1 1/8- 7	2.805	6	2/12
ATR11212B	ATR11212Z		ATR11212HD	1 1/8- 7	2.805	12	2/24
ATR12506B	ATR12506Z			1 1/4- 7	3.5	6	1/6
ATR12512B	ATR12512Z		ATR12512HD	1 1/4- 7	3.5	12	1/12
ATR15006B	ATR15006Z			1 1/2- 6	5.05	6	1/6
ATR15012B	ATR15012Z		ATR15012HD	1 1/2- 6	5.05	12	1/12

* HDG Rod must use an oversized nut!